

US010817594B2

# (12) United States Patent

Setlak et al.

(54) WEARABLE ELECTRONIC DEVICE
HAVING A LIGHT FIELD CAMERA USABLE
TO PERFORM BIOAUTHENTICATION
FROM A DORSAL SIDE OF A FOREARM
NEAR A WRIST

(71) Applicant: Apple Inc., Cupertino, CA (US)

(72) Inventors: Dale Setlak, Merritt Island, FL (US);

Giovanni Gozzini, Berkeley, CA (US); Manohar B. Srikanth, Mountain View,

CA (US); Mohammad Yeke Yazdandoost, San Jose, CA (US)

(73) Assignee: Apple Inc., Cupertino, CA (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35

U.S.C. 154(b) by 113 days.

(21) Appl. No.: 16/132,241

(22) Filed: Sep. 14, 2018

(65) **Prior Publication Data** 

US 2019/0095602 A1 Mar. 28, 2019

# Related U.S. Application Data

- (60) Provisional application No. 62/564,916, filed on Sep. 28, 2017.
- (51) **Int. Cl. G06F 21/32** (2013.01) **G06F 1/16** (2006.01)
  (Continued)
- (58) Field of Classification SearchCPC combination set(s) only.See application file for complete search history.

# (10) Patent No.: US 10,817,594 B2

(45) **Date of Patent:** Oct. 27, 2020

# (56) References Cited

#### U.S. PATENT DOCUMENTS

4,437,089 A 3/1984 Achard 5,903,350 A 5/1999 Bush et al. (Continued)

#### FOREIGN PATENT DOCUMENTS

CN 1603987 4/2005 CN 101639800 2/2010 (Continued)

# OTHER PUBLICATIONS

Pascual et al., "Capturing Hand or Wrist Vein Images for Biometric Authentication Using Low-Cost Devices," Sixth International Conference on Intelligent Information Hiding and Multimedia Signal Processing, Carlos III University of Madrid, Electronics Technology Department, 2010, 5 pages.

(Continued)

Primary Examiner — Omar S Ismail (74) Attorney, Agent, or Firm — Brownstein Hyatt Farber Schreck, LLP

### (57) ABSTRACT

A method of authenticating a user of a wearable electronic device includes emitting light into a dorsal side of a forearm near a wrist of the user; receiving, using a light field camera, remissions of the light from the dorsal side of the forearm near the wrist of the user; generating a light field image from the remissions of the light; performing a synthetic focusing operation on the light field image to construct at least one image of at least one layer of the forearm near the wrist; extracting a set of features from the at least one image; determining whether the set of features matches a reference set of features; and authenticating the user based on the matching. In some embodiments, the method may further include compensating for a tilt of the light field camera prior to or while performing the synthetic focusing operation.

# 23 Claims, 16 Drawing Sheets

